



COLD CLIMATE HEAT PUMP



Flexible

Side discharge, small footprint, **24VAC** compatible

Comfortable

Quiet operation, optimal performance from **-5°C** to **53°C**

Efficient

Up to **20 SEER/10.5 HSPF**

Adjustable

2/3 and **4/5** ton outdoor unit options

Cold Climate

-100% heat to **-5°C**



Qualifies
for \$5K in
Rebates

Canada
**Greener
Homes**
Initiative



EASY
INSTALLATION



ENERGY
EFFICIENT



QUIET
OPERATION



SMALL
FOOTPRINT



ULTRA
PERFORMANCE

ENERMAXX

**BOSCH INVERTER
DUCTED SPLIT SYSTEM IDS 2.0**

DAIKIN FIT

FUJITSU HALCYON MPAH

	ENERMAXX	BOSCH INVERTER DUCTED SPLIT SYSTEM IDS 2.0	DAIKIN FIT	FUJITSU HALCYON MPAH
CAPACITY	24K - 60K (FIELD CONFIGURABLE)	24K - 60K (FIELD CONFIGURABLE)	18K - 60K (INDIVIDUAL UNITS)	24K - 48K (INDIVIDUAL UNITS)
EFFICIENCY	UP TO 20 SEER / 10.5 HSPF	UP TO 20.5 SEER / 10.5 HSPF	UP TO 18 SEER / 10.0 HSPF	UP TO 19 SEER / 10.7 HSPF
HEATING RANGE	-30°C (-22°F) TO 24°C (75°F)	-20°C (-4°F) TO 30°C (86°F)	-29°C (-20°F) TO 21°C (70°F)	-20.5°C (-5°F) TO 24°C (75°F)
COOLING RANGE	-15°C (5°F) TO 54°C (129°F)	-9.4°C (15°F) TO 51.7°C (125°F)	-17.8°C (0°F) TO 46.1°C (115°F)	-20.5°C (-5°F) TO 46.1°C (115°F)
FLEXIBLE SIZING OF OUTDOOR UNIT	24/36K OR 48/60K (FIELD CONFIGURABLE)	24/36K OR 48/60K (FIELD CONFIGURABLE)	18/24/30/36/42/48/60K (INDIVIDUAL UNITS)	24/30/36/48K (INDIVIDUAL UNITS)
24VAC INTERFACE	YES (FACTORY INSTALLED)	YES (FACTORY INSTALLED)	NO (PROPRIETARY CONTROL REQUIRED)	YES (FIELD INSTALLED OPTION)
OUTDOOR UNIT DISCHARGE DESIGN	HORIZONTAL	VERTICAL	HORIZONTAL	HORIZONTAL
SMALL, NARROW FOOTPRINT OF OU	YES	NO	YES	YES
SOUND LEVEL OF OU	DOWN TO 55 DB(A)	DOWN TO 56 DB(A)	DOWN TO 60 DB(A)	DOWN TO 53 DB(A)
AUXILIARY HEAT STRIPS AVAILABLE	YES (FIELD INSTALLED)	YES (FIELD INSTALLED)	YES (FIELD INSTALLED)	YES (FIELD INSTALLED)
PRE-CHARGED LENGTH	9.4 m.	4.7 m.	4.6 TO 7.6 m.	20.1 m.
PIPE LENGTH (MIN/MAX)	4.5 / 50 m.	4.5 / 45 m.	4.5 / 30 m.	4.9 / 50 m.
MAX. PIPE ELEVATION	30 m.	15 m.	27 m.	30 m.
A COIL OPTION	YES	YES	YES	YES